

18

Product ID: 2575DM29341



2575-23



0359-23

C11
C31
C91

Produced at:
RAIS A/S, Industrivej 20, 9900 Frederikshavn, Danmark

- Visio Gas 160 F Visio Gas 160 LC
 Visio Gas 160 RC Visio Gas 160 3S

(VISIO 5)

This appliance must be installed in accordance with the rules in force, and only used in a sufficiently ventilated space. Consult instructions before installation and use of this appliance. Tested and Certified for use on Biopropane. Efficiency class 1.

Serial number _____ Burner ID. _____

Gas category and supply pressure			Input (Hi, kW)	Output (Hi, kW)	Burner pressure high (Hot)	Country of destination
<input type="checkbox"/> N A T U R A L G A S	I2H/ I2E	G20 @ 20 mbar	16,2	13,2	12,5 Interval 11,3 - 13,8	AT, CH, CZ, DE, DK, EE, ES, FI, GB, GR, HR, IE, IT, LT, LU, LV, NO, PL, PT, RO, SE, SI, SK, TR
	I2ELL	G25 @ 20 mbar	13,1	10,6	12,5 11,3 - 13,8	DE
	I2E+	G20@20 mbar	16,2	13,2	12,5 11,3 - 13,8	BE, FR
	I2E+	G25@25 mbar	14,6	11,8	16 14,4 - 17,6	BE, FR
	I2L / I2EK / I2 (43,46-45,3 MJ/m ³ Oc)	G25.3 @ 25 mbar	14,7	11,9	16,2 14,6 - 17,8	NL

<input type="checkbox"/> L P G	I3+ (28-30/37)	G30@28-30 mbar	20,7	16,7	27 Interval 24,3 - 29,7	BE, CH, CY, CZ, ES, FR, GB, GR, IE, IT, PT, SI, SK, TR
	I3+ (28-30/37)	G31@37 mbar	20	16	33 29,7 - 36,3	BE, CH, CY, CZ, ES, FR, GB, GR, IE, IT, PT, SI, SK, TR
	I3P (30)	G31@30 mbar	18,5	14,6	26 23,4 - 28,6	FI, NL, RO
	I3P (37)	G31@37 mbar	20	16	33 29,7 - 36,3	BE, CH, CZ, ES, FR, GB, GR, HR, IE, IT, LT, NL, PL, PT, SL, SK, TR
	I3P (50)	G31@50 mbar	20	16	33 29,7 - 36,3	AT, CH, CZ, DE, NL, SK
	I3B/P (30)	G30@30 mbar	20,7	16,7	27 24,3 - 29,7	BE, BG, CY, DK, EE, FI, FR, GB, GR, HR, HU, IT, LT, MT, NL, NO, RO, SE, SI, SK, TR
	I3B/P (30)	G31@30 mbar	18,5	14,6	26 23,4 - 28,6	BE, BG, CY, DK, EE, FI, FR, GB, GR, HR, HU, IT, LT, MT, NL, NO, RO, SE, SI, SK, TR
	I3B/P (50)	G30/G31@50	20	16	33 29,7 - 36,3	AT, CH, CZ, DE, FR, SK

Produced for:
ATTIKA FEUER AG, Brunnmatt 16, CH-6330 Cham / RAIS A/S, Industrivej 20, DK-9900 Frederikshavn